

Homepage

SEARCH PRODUCT BY TYPE

- > Masking & Paper Tapes
- > Foil & Film Tapes
- > Packaging Tapes
- > Packaging Dispensers & Equipment
- > Double-Coated Tapes
- > Cloth & Duct Tapes
 - > Contractor Grade Duct Tapes
 - > Utility Grade Duct Tapes
 - > Industrial Grade Duct Tapes
 - > HVAC Grade Duct Tapes
 - > Premium Grade Duct Tapes
- > Arts & Entertainment Cloth Tapes
 - > PC 628
 - > PC 660
 - > P- 665
 - > P- 68
 - > P- 672
 - > P- 691
- > Colored Cloth & Duct Tapes
- > Specialty Tapes



[Click To View Larger](#)

P- 665

Vinyl-coated gaffer's tape

Wide color variety

ASTM D5486M Type IV Class I (replaced PPP-T-60E Type IV Class I - canceled 1995); ASTM 1586A

11.5 mil vinyl-coated gaffer's tape, available in a wide variety of colors, used in the Arts & Entertainment industry to hold wiring, lighting, and props. Other applications include color coding, seaming, bundling, and protection.

MARKETS

- >Arts & Entertainment
- >Industrial

TYPICAL APPLICATIONS

- >Gaffer's tape
- >Holding wiring, lighting, and props
- >Color-coding

COLORS



[Click To Open Available Sizes Chart](#)

PHYSICAL PROPERTIES

	Standard	Metric	ASTM Test Method
Tensile Strength	48 lbs/in width	84.1 N/10 mm	D 3759 D 3759M
Adhesion to Stainless Steel	80 oz/in width	8.76 N/10 mm	D 3330 D 3330M
Thickness	11.5 mils	0.29 mm	D 3652 D 3652M
Service Temperature Min	45 °F	7 °C	N/A
Service Temperature Max	200 °F	93 °C	N/A

Values obtained from tests do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages.

Shurtape recommends the user to determine whether the product is fit

Shurtape recommends the user to determine whether the product is fit for a particular purpose and is suitable for the users method of application.

RELATED PRODUCTS

> [PC 628](#)

> [P- 691](#)

[Download MSDS Sheet](#)

[Download Technical Data Sheet](#)

[Download Environmental Compliance Letter](#)